

TECHNICAL MANUAL
TM 5-820-3
Air Force Manual
AFM 88-5, Chapter 3

HEADQUARTERS
DEPARTMENTS OF THE
ARMY AND THE AIR FORCE
WASHINGTON, DC, 3 June 1991

DRAINAGE AND EROSION-CONTROL STRUCTURES FOR AIRFIELDS AND HELIPORTS

Approved for public release; Distribution is unlimited

		<i>Paragraph</i>	<i>Page</i>
CHAPTER	1. INTRODUCTION		
	Purpose	1-1	1-1
	Scope	1-2	1-4
	Reference	1-3	1-1
	Problem areas	1-4	1-1
	Design	1-5	1-1
	Outfall considerations	1-6	1-1
	Drainage law	1-7	1-1
CHAPTER	2. DRAINAGE PIPE		
	General	2-1	2-1
	Selection of type of pipe	2-2	2-1
	Selection of n values	2-3	2-1
	Restricted use of bituminous coated pipe	2-4	2-2
	Minimum and maximum cover	2-5	2-2
	Frost condition considerations	2-6	2-9
	Infiltration of fine soils through drainage pipe joints	2-7	2-10
CHAPTER	3. INLETS AND BOX DRAINS		
	General	3-1	3-1
	Inlets versus catch basins	3-2	3-1
	Design features	3-3	3-1
	Box drains	3-4	3-5
	Settlement of inlets and drains	3-5	3-8
	Gutters	3-6	3-8
	Curb inlets	3-7	3-8
	Clogging	3-8	3-8
	Ladders	3-9	3-8
CHAPTER	4. GUTTERS		
	General	4-1	4-1
	Discharge capacity	4-2	4-1
	Design charts	4-3	4-4
CHAPTER	5. STORM DRAINS AND CULVERTS		
	General	5-1	5-1
	Headwalls and endwalls	5-2	5-1
	Scour at outlets	5-3	5-3
	Erosion control at outlet	5-4	5-11
CHAPTER	6. OPEN CHANNELS		
	General	6-1	6-1
	Channel design	6-2	6-1
	Design procedure	6-3	6-4
	Drop structures and check dams	6-4	6-4
CHAPTER	7. CHUTES		
	General	7-1	7-1
	Design	7-2	7-2
	Design problem	7-3	7-6
CHAPTER	8. CONSTRUCTION DRAINAGE		
	General	8-1	8-1
	Planning	8-2	8-1
	Environmental degradation	8-3	8-1
	Protective measures	8-4	8-1

*This manual supersedes TM 5-820-3, dated 30 January 1978.

	<i>Paragraph</i>	<i>Page</i>
APPENDIX A. REFERENCES		A-1
Appendix B. COVER TABLES		B-1
APPENDIX C. OUTLET PROTECTION DESIGN PROBLEM		C-1
APPENDIX D. CHANNEL DESIGN PROBLEM		D-1
APPENDIX E. NOTATION		E-1
BIBLIOGRAPHY		BIBLIO-1

List of Figures

<i>Figure No.</i>	<i>Title</i>	<i>Page</i>
2-1	Three main classes of conduits	2-5
2-2	Free-body conduit diagrams	2-6
2-3	Trench beddings for circular pipe	2-7
2-4	Beddings for positive projecting conduits	2-8
2-5	Installation conditions which influence loads on underground conduits	2-9
3-1	Determination of typical inlet grating discharge curve	3-2
3-2	Examples of typical inlet grates	3-3
3-3	Examples of inlet design	3-4
3-4	Typical inlet and box drain designs for airfield and heliport storm drainage systems	3-6
3-5	Repair box drains	3-7
4-1	Drainage gutters for runways and aprons	4-2
5-1	Culvert Head walls and wingwalls	5-2
5-2	Types of scour at storm-drain and culvert outlets	5-3
5-3	Square culvert-Froude number	5-5
5-4	Predicted scour depth versus observed scour depth	5-6
5-5	Predicted scour width versus observed scour width	5-7
5-6	Predicted scour length versus observed scour length	5-8
5-7	Predicted scour volume versus observed scour volume	5-9
5-8	Dimensionless scour hole geometry for minimum tailwater	5-10
5-9	Dimensionless scour hole geometry for maximum tailwater	5-11
5-10	Recommended size of protective stone	5-12
5-11	Length of stone protection, horizontal blanket	5-13
5-12	Recommended configuration of riprap blanket subject to minimum and maximum tailwaters	5-14
5-13	Preformed scour hole	5-15
5-14	Culvert outlet erosion protection, lined channel expansion	5-16
5-15	Maximum permissible discharge for lined channel expansions	5-17
5-16	Flared outlet transition	5-18
5-17	Stilling well	5-19
5-18	US Bureau of Reclamation impact basin	5-20
5-19	Saint Anthony Falls stilling basin	5-21
5-20	Design chart for SAF stilling basin	5-23
5-21	Recommended riprap sizes	5-25
5-22	Scour hole riprap-sizes	5-26
6-1	Retardance coefficients for flow in turfed channels	6-3
6-2	Details and design chart for typical drop structure	6-5
7-1	Details and typical drainage chute	7-2
7-2	Details of typical drop intake	7-3
7-3	Drop structure calibration curves	7-4
7-4	Air entrainment in chute flow	7-5
7-5	Design problem-solution one	7-7
7-6	Design problem-solution two	7-8
D-1	Froude number and depth of flow required for incipient transport of cohesionless material	D-2
D-2	Depth of flow and unit discharge for incipient transport of cohesionless material	D-3
D-3	Flow characteristics of trapezoidal channels with IV-on-3H side slopes	D-4
D-4	Froude number and depth of flow for incipient failure of riprap-lined channel	D-5
D-5	Depth of flow and unit discharge for incipient failure of riprap-lined channel	D-6
D-6	Flow characteristics of rectangular channels	D-8
D-7	Discharge characteristics of various channels	D-9

List of Tables

<i>Table No.</i>	<i>Title</i>	<i>Page</i>
2-1	Roughness coefficients for various pipes	2-2
2-2	Maximum cover height reduction factors for riveted and bolted seams	2-4
6-1	Suggested coefficients of roughness and maximum permissible mean velocities for open channels in military construction	6-2
B-1	Suggested maximum cover requirements (feet) for 1½- by ¼-inch corrugated steel pipe	B-2
B-2	Suggested maximum cover requirements (feet) for 2 2/3- by ½-inch corrugated steel pipe	B-3
B-3	Suggested maximum cover requirements (feet) for 3- by I-inch corrugated steel pipe	B-4
B-4	Suggested maximum cover requirements (feet) for 5- by 1-inch corrugated steel pipe	B-6
B-5	Suggested maximum cover requirements (feet) for 6- by 2-inch corrugated steel pipe	B-8
B-6	Suggested minimum cover requirements (feet) for 1½- by ¼-inch corrugated steel pipe	B-9
B-7	Suggested minimum cover requirements (feet) for 2 2/3- by ½-inch corrugated steel pipe	B-10
B-8	Suggested minimum cover requirements (feet) for 3- by I-inch corrugated steel pipe	B-14
B-9	Suggested minimum cover requirements (feet) for 5- by 1-inch corrugated steel pipe	B-18
B-10	Suggested minimum cover requirements (feet) for 6- by 2-inch corrugated steel pipe	B-22
B-11	Suggested maximum cover requirements (feet) for 2%- by ½-inch corrugated aluminum pipe	B-26
B-12	Suggested maximum cover requirements (feet) for 3- by I-inch corrugated aluminum pipe	B-27
B-13	Suggested maximum cover requirements (feet) for 6- by I-inch corrugated aluminum pipe	B-30
B-14	Suggested minimum cover requirements (feet) for 2%- by 2/2-inch corrugated aluminum pipe	B-33
B-15	Suggested minimum cover requirements (feet) for 3- by I-inch corrugated aluminum pipe	B-37
B-16	Suggested minimum cover requirements (feet) for 6- by 1-inch corrugated aluminum pipe	B-41
B-17	Suggested cover requirements for corrugated polyethylene (PE) pipe	B-45
B-18	Maximum feet of cover for reinforced-concrete culverts	B-46
B-19	Minimum feet of cover for reinforced-concrete culverts	B-49
B-20	Maximum feet of cover for nonreinforced-concrete culverts	B-57
B-21	Minimum feet of cover for nonreinforced-concrete culverts	B-65
B-22	Maximum feet of cover for vitrified clay culverts	B-73
B-23	Minimum feet of cover for vitrified clay culverts	B-80